

Factory Installed Cable Connectors

B2A
2 Socket,
Silicone Seal
Tight Boot
**Polycarbonate
Insert**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Common (-)	250° F (121° C)	CB102, CB103, CB110, CB111, CB202, CB206

IP66

Build To Order

B3A
3 Socket,
Silicone Seal
Tight Boot
**Polycarbonate
Insert**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Common (-) C = Signal (+)	250° F (121° C)	CB105, CB112, CB212, CB218

IP66

Build To Order

B2N
2 Socket,
Silicone Seal
Tight Boot
Nylon Insert

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Common (-)	250° F (121° C)	CB102, CB103, CB110, CB111, CB202, CB206

IP66

Build To Order

B3N
3 Socket,
Silicone Seal
Tight Boot
Nylon Insert

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Common (-) C = Signal (+)	250° F (121° C)	CB105, CB112, CB212, CB218

IP66

Build To Order

B2R
2 Socket,
Silicone Seal
Tight Boot
**Polyphenylene Sulfide
(PPS) Insert**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Common (-)	392° F (200° C)	CB102, CB103, CB110, CB111, CB202, CB206

IP66

Build To Order

B3R
3 Socket,
Silicone Seal
Tight Boot
**Polyphenylene Sulfide
(PPS) Insert**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Common (-) C = Signal (+)	392° F (200° C)	CB105, CB112, CB212, CB218

IP66

Build To Order

C79
TNC
Connector
Epoxied

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	A = Signal (+) B = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111

IP66

Build To Order

D2C
2 Socket,
MIL-Style
**Polyurethane
Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	A = Signal (+) B = Common (-)	250° F (121° C)	CB103, CB104, CB108, CB110

IP66

Build To Order

D3C
3 Socket,
MIL-Style
**Polyurethane
Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	A = Signal (+) B = Common (-) C = Signal (+)	250° F (121° C)	CB105, CB117

IP66

Build To Order

D2CG*
2 Socket,
MIL-Style
**Polyurethane
Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	A = Signal (+) B = Common (-)	250° F (121° C)	CB103, CB104, CB108, CB110

IP66

Build To Order

*Grounded To Sensor Case

