

# LP204-M12E Series

Loop Power Sensor, 4-20 mA Output Proportional to Vibration in Velocity, Side Exit 4 Pin M12 Connector



VIBRATION ANALYSIS HARDWARE



## Product Features


4-20 mA Current Proportional to Vibration in Velocity

- ▶ Transmit Signals Over Long Distances with No Signal Loss
- ▶ Outputs to PLC, DCS, SCADA

### LP204-XXX-M12E

4 Pin Connector

Connector Pin	Polarity
1	(+) Signal/Power
2	(-) Common
3	Not Used
4	Not Used



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	LP204-M12E	M/LP204-M12E	<b>Physical</b>		
Tolerance: 4 mA		(± 10%)	Sensing Element		PZT Ceramic
Tolerance: 20 mA		(± 10%)	Sensing Structure		Shear Mode
<b>Electrical</b>			Weight	4.7 oz	134 grams
Settling Time		<30 Seconds	Case Material		316L Stainless Steel
Voltage Source (IEPE)		15-30 VDC	Mounting Thread		1/4-28
Case Isolation		>10 <sup>8</sup> ohm	Connector (Non-Integral)		4 Pin M12
<b>Environmental</b>			Mounting Torque	2 to 5 ft. lbs.	2.7 to 6.8 Nm
Operating Temperature Range	-4 to 212°F	-20 to 100°C	Mounting Hardware Supplied	1/4-28 Captive Bolt	M6x1 Captive Bolt
Electromagnetic Sensitivity		CE	Calibration Certificate		Current Output @ 100 Hz
Sealing		Welded, Hermetic			

## Ordering Information

Integral Options						
<input type="checkbox"/>	/LP204 -	<input type="checkbox"/>	<input type="checkbox"/>	-	<input type="checkbox"/>	/ <input type="checkbox"/>
<b>Bolt Type</b>	<b>Measurement Range</b>	<b>Type</b>	<b>Frequency Range ±3dB</b>	<b>Style</b>	<b>Armor Length (Integral)</b>	<b>Cable Length (Integral)</b>
Blank = 1/4-28 M = M6x1	0 = 0-0.5 IPS (0-12.7 mm/sec) 1 = 0-1 IPS (0-25.4 mm/sec) 2 = 0-2 IPS (0-50.8 mm/sec) 3 = 0-0.4 IPS (0-10 mm/sec) 4 = 0-0.8 IPS (0-20 mm/sec) 6 = 0-5 IPS (0-127 mm/sec)	P = Peak R = RMS	1 = 600-60000 CPM (10-1000 Hz) 2 = 180-150000 CPM (3-2500 Hz) 3 = 180-60000 CPM (3-1000 Hz) 4 = 180-300000 CPM (3-5000 Hz) 5 = 180-600000 CPM (3-10000 Hz)	1E = 2 Pin MIL C-5015 2E = Integral Cable 3E = Armor Jacket M12E = 4 Pin M12	010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m	010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m
*Custom Lengths Available Upon Request						

www.delta3n.hu

Backed by our Unconditional Lifetime Warranty & Free Annual Recalibration Service

www.ctconline.com | sales@ctconline.com | 585-924-5900