



























# Connector Kits for Field Installation

Part #	Installed Connector Side View	Connector Kit Parts	Connector Kit Parts #	Diameter	Max Temp.	Compatible Cables
<b>CF-FX</b> <i>Supplied with epoxy and syringe (MH109-3A)</i>		 Stock Product BNC Plug Connector Kit	CF-FX	.250" (6,4 mm)	250°F (121°C)	CB102, CB103 CB110, CB111
<b>CF-EX</b> <i>Supplied with epoxy and syringe (MH109-3A)</i>		 Stock Product BNC Jack Connector Kit	CF-EX	.250" (6,4 mm)	250°F (121°C)	CB102, CB103 CB110, CB111
<b>CF-F</b>		 Stock Product BNC Plug Connector Kit	CF-F	.250" (6,4 mm)	250°F (121°C)	CB102, CB103 CB110, CB111
<b>CF-E</b>		 Stock Product BNC Jack Connector Kit	CF-E	.250" (6,4 mm)	250°F (121°C)	CB102, CB103 CB110, CB111
<b>CF-EMPP</b>		 Stock Product BNC Jack Connector Kit	CF-EMPP	.250" (6,4 mm)	250°F (121°C)	CB102, CB103 CB110, CB111, CB202, CB206 CB802, CB806 CB810, CB811
<b>CF-G3H-250</b>		 Stock Product 3 Socket Connector Kit	CF-G3H-250	≤.250" (6,4 mm)	250°F (121°C)	CB105, CB117 CB119, CB212
<b>CF-G4H1-250</b>		 Stock Product 4 Socket Connector Kit	CF-G4H1-250	≤.250" (6,4 mm)	250°F (121°C)	CB105, CB112 CB117, CB218
<b>CC-J2A-175</b> <b>CC-J2A-190</b> <b>CC-J2A-250</b> <i>Supplied with epoxy and syringe (MH109-3A)</i>		 Stock Product 2 Socket mini-MIL Connector Kit	CC-J2A-175 CC-J2A-190 CC-J2A-250	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm)	250°F (121°C) 250°F (121°C) 250°F (121°C)	CB102, CB110 CB111 CB103, CB206
<b>CC-J4A-190</b> <b>CC-J4A-250</b> <i>Supplied with epoxy and syringe (MH109-3A)</i>		 Stock Product 4 Socket mini-MIL Connector Kit	CC-J4A-190 CC-J4A-250	.190" (4,8 mm) .250" (6,4 mm)	250°F (121°C) 250°F (121°C)	CB119 CB105, CB218
<b>CF-R2C-175</b> <b>CF-R2C-190</b> <b>CF-R2C-250</b> <i>Supplied with epoxy and syringe (MH109-3A)</i>		 Stock Product 2 Pin Connector Kit	CF-R2C-175 CF-R2C-190 CF-R2C-250	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm)	250°F (121°C) 250°F (121°C) 250°F (121°C)	CB102, CB110 CB111 CB103, CB206
<b>CF-SF</b> <i>Supplied with epoxy and syringe (MH109-3A)</i>		 Stock Product 3 Pin/Socket Safety Feature Kit	CF-SF	.250" (6,4 mm)	250°F (121°C)	CB102, CB103 CB104, CB108, CB110, CB111
<b>CF-SFT</b> <i>Supplied with epoxy and syringe (MH109-3A)</i>		 Stock Product 5 Pin/Socket Safety Feature Kit	CF-SFT	.250" (6,4 mm)	250°F (121°C)	CB105, CB112, CB119
<b>MH109-3A</b>		 Stock Product * For use with Field Installable Connector Kits Potting Adhesive, 10 g, with 10 ml Syringe	MH109-3A	N/A	392°F (200°C)	N/A