

Adhesives/Accessories

Product Purpose

Industrial Grade Adhesives for Permanently Installing Mounting Pads

Field tested under the most adverse and hazardous conditions. All of our adhesives have been proven to withstand the demands of their specific applications.

MH109-1A

8.45 oz (250 ml) Tube with
4.5 oz. (128 g) Spray Activator



MH109-1B

.85 oz. (25 ml) Syringe with
.88 oz. (25 g) Spray Activator



MH109-2A

.85 oz. (25 ml) 2 in 1 tube



Part No.	Adhesive	Manufacturer/ Brand	Set Up Time	Thin Layer Bonding	Gap Filling	No. of Applications	Temperature Range
MH109-1A	Resin with Spray Activator	Loctite Depend	1 Minute	Yes	No	250-500	-60° to 250°F (-51° to 121°C)
MH109-1B	Resin with Spray Activator	Loctite Depend	1 Minute	Yes	No	25-50	-60° to 250°F (-51° to 121°C)
MH109-2A	2 Part Epoxy with 2 Barrel Tube Dispenser	Devcon Plastic Welder	2-3 Minutes	Yes	Yes	*2-20	-60° to 250°F (-51° to 121°C)

* Gap filling applications require additional adhesive, and reduce the number of applications possible.