

Factory Installed Cable Connectors

Section 2 - Cables & Connectors

E
BNC Jack, Molded
Poly-carbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

IP66

Build To Order

EX
BNC Jack
Epoxyed

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

IP66

Build To Order

E3C
3 BNC Jacks to 1 Multi-Conductor Cable
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

* Complete Technical Drawing Available on Page 137

Build To Order

F
BNC Plug
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

Build To Order

F2C
2 BNC Plugs to 1 Multi-Conductor Cable
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

* Complete Technical Drawing Available on Page 137

Build To Order

EMPP
BNC Measurement Point with Protector
Nylon Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB110, CB111, CB202, CB206, CB802, CB806, CB810, CB811

IP66

Protector helps shield connector from environmental hazards

Build To Order

E2C
2 BNC Jacks to 1 Multi-Conductor Cable
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

* Complete Technical Drawing Available on Page 137

IP66

Build To Order

E4C
4 BNC Jacks to 1 Multi-Conductor Cable
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

* Complete Technical Drawing Available on Page 137

Build To Order

FX
BNC Plug
Epoxyed

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

Build To Order

F3C
3 BNC Plugs to 1 Multi-Conductor Cable
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

* Complete Technical Drawing Available on Page 137

Build To Order

Factory Installed Cable Connectors

F4C

4 BNC Plugs to 1 Multi-Conductor Cable
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119



Build To Order

* Complete Technical Drawing Available on Page 137

FX90

Right Angle BNC Plug
Epoxied

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206



Build To Order

* Complete Technical Drawing Available on Page 137

FX92

2 Right Angle BNC Plugs to 1 Multi-Conductor Cable
Epoxied

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB112, CB117, CB212,



Build To Order

* Complete Technical Drawing Available on Page 137

FX93

3 Right Angle BNC Plugs to 1 Multi-Conductor Cable
Epoxied

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119, CB218,



Build To Order

* Complete Technical Drawing Available on Page 137

G3H

3 Socket, Twist Lock

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	A = Signal (+) B = Common (-) C = Signal (+) White	250° F (121° C)	CB105, CB112, CB117, CB218



Build To Order

G4H1

4 Socket, Twist Lock

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	A = Ch. 1 (+) B = Ch. 2 (+) C = Ch. 3 (+) D = Common (-)	250° F (121° C)	CB105, CB117, CB218



Build To Order

J2A

2 Socket, mini-MIL
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Common (-)	250° F (121° C)	CB102, CB103, CB110, CB111, CB206



Build To Order

IP66

J4A

4 Socket, mini-MIL
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Ch. Y (+) B = Ch. X (+) C = Ch. Z (+) D = Common (-)	250° F (121° C)	CB105, CB117, CB119, CB218



Build To Order

IP66

J2C

2 Socket, mini-MIL
Polyurethane Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	A = Signal (+) B = Common (-)	250° F (121° C)	CB108, CB110, CB206



Build To Order

J4C

4 Socket, mini-MIL
Polyurethane Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	A = Ch. Y (+) B = Ch. X (+) C = Ch. Z (+) D = Common (-)	250° F (121° C)	CB105, CB117, CB119



Build To Order

