

Armor & Hydraulic Hose Protected Cabling

Part No.	Jacket Material	Use	Conductor Qty.	Shielding Method	Max Temp.	Cable Diameter Weight/Ft.	Wire Gauge	Ratings/Certifications
CB802	Red Teflon® with Stainless Steel Braided Shield sheathing	Permanent Monitoring	2 Conductor	Foil with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .175 in (4,5 mm) 1.5 lbs./30 ft.	AWG = 20	UL RoHS HIGH TEMP
				Compatible Connectors: A2A, A2E, A2N, A2P, A2R, A2S, A2V, B2A, B2R, D2H, D2J, E, EX, EMPP, F, FHD, FX, FX90, J2A, J2C, J2P, R2C, L, Z				
Maximum Sheathing Length: 30 ft (10 m)								
CB806	Red Teflon® with Stainless Steel Braided Shield sheathing	Permanent Monitoring	2 Conductor	Foil with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .175 in (4,5 mm) 4.0 lbs./100 ft.	AWG = 20	RoHS HIGH TEMP
				Compatible Connectors: A2A, A2E, A2N, A2P, A2R, A2S, A2V, B2A, B2R, D2H, D2J, E, EX, EMPP, F, FHD, FX, FX90, J2A, J2C, J2P, R2C, L, Z				
Maximum Sheathing Length: 100 ft (30 m)								
CB810	Black Polyurethane Light Weight with Stainless Steel Braided Shield sheathing	Permanent Monitoring	2 Conductor	Braided Shield with Drain Wire	250°F (121°C)	.250 in (6,4 mm), .175 in (4,5 mm) 1.6 lbs./25 ft.	AWG = 20	UL RoHS
				Compatible Connectors: A2A, A2E, A2N, A2P, A2R, A2V, B2A, B2R, D2C, D2CG, D2D, D2H, E, EX, EMPP, F, FHD, FX, FX90, J2A, J2C, J2P, R2C, L, Z				
Maximum Sheathing Length: 25 ft (8 m)								
CB811	Yellow Teflon® with Stainless Steel Braided Shield sheathing	Permanent Monitoring	2 Conductor	Braided Shield with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .190 in (4,8 mm) 1.6 lbs./25 ft.	AWG = 20	UL RoHS HIGH TEMP
				Compatible Connectors: A2A, A2E, A2N, A2P, A2R, A2S, A2V, B2A, B2R, D2C, D2H, D2J, E, EX, EMPP, F, FHD, FX, FX90, J2A, J2C, J2P, K2C, R2C, L, Z				
Maximum Sheathing Length: 25 ft (8 m)								
CB812	White Teflon® with Stainless Steel Braided Shield sheathing	Permanent Monitoring	3 Conductor	Foil with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .190 in (4,8 mm) 1.7 lbs./25 ft.	AWG = 20	UL RoHS HIGH TEMP
				Compatible Connectors: A3A, A3E, A3N, A3P, A3R, A3S, A3V, B3A, B3B, B3R, D3H, E2C, F2C, G3H, L, Z				
Maximum Sheathing Length: 25 ft (8 m)								
CB818	Red Teflon® with Stainless Steel Braided Shield sheathing	Permanent Monitoring	4 Conductor	Foil with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .148 in (3,8 mm) 5.1 lbs./100 ft.	AWG = 22	RoHS HIGH TEMP
				Compatible Connectors: A3A, A3N, A3R, A3S, A3V, D3H, E2C, E3C, F2C, F3C, G4H1, J4A, J4P, L, Z				
Maximum Sheathing Length: 100 ft (30 m)								
CB819	Orange Teflon® with Stainless Steel Braided Shield sheathing	Permanent Monitoring	4 Conductor	Foil with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .190 in (4,8 mm) 1.4 lbs./25 ft.	AWG = 22	UL RoHS HIGH TEMP
				Compatible Connectors: A3A, E2C, E3C, F2C, F3C, G4H1, J4A, J4P, L, Z				
Maximum Sheathing Length: 25 ft (8 m)								

* Teflon® is a registered trademark of DuPont.

