

ISOLATED BNC CORDSETS STRAIGHT & COILED BNC TO BNC

Example Cordset: CB104-FN-010-FN














Black polyurethane jacketed coiled cable, with Isolated BNC plug connector to Isolated BNC plug connector, 10 foot length extended



Example Cordset: CB103-FN-005-FN-SF

Black polyurethane jacketed cable, with Isolated BNC plug connector to Isolated BNC plug connector, with safety connector, 5 foot length



CB <input type="text"/> - <input type="text"/> - <input type="text"/> - <input type="text"/> - <input type="text"/>	Connector Part Number (see <i>Factory Installed Connectors</i> data sheet)	Cable Length (three digit format)	Terminating Connector Part Number (see <i>Factory Installed Connectors</i> data sheet)	Safety Connector (see page 119 for Safety Connector information)
<p>CB103</p>  <p>Black Polyurethane 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .245 in (6 mm) AWG = 20</p> <p>CB104</p>  <p>Black Polyurethane, Coiled 2 Conductor Braided Shield 250°F (121°C) .210 in (5 mm) AWG = 22</p> <p>CB108</p>  <p>Black Polyurethane, Light weight, Coiled 2 Conductor Braided Shield 250°F (121°C) .170 in (4 mm) AWG = 24</p> <p>CB110</p>  <p>Black Polyurethane, Light weight, 2 Conductor Braided Shield with Drain Wire 250°F (121°C) .175 in (4 mm) AWG = 20</p>	<p>EN  Build To Order</p> <p>Isolated BNC Jack Connector Portable Measurements, Permanent Mount</p> <p>ENX  Build To Order</p> <p>Isolated BNC Jack Connector, Epoxy Filled Portable Measurements, Permanent Mount</p> <p>FN  Build To Order</p> <p>Isolated BNC Plug Connector Portable Measurements, Permanent Mount</p> <p>FNX  Build To Order</p> <p>Isolated BNC Plug Connector, Epoxy Filled Portable Measurements, Permanent Mount</p> <p>NOTE: The BNC connectors above feature a floating shield drain wire that is not case grounded</p>	<p>Select Cable Length Based on Three Digit Numbering System Example Numbering:</p> <p>001 = 1 ft. (.30 m) 005 = 5 ft. (1.52 m) 010 = 10 ft. (3.05 m) 015 = 15 ft. (4.57 m) 025 = 25 ft. (7.62 m) 050 = 50 ft. (15.24 m) 100 = 100 ft. (30.48 m)</p> <p>Straight Cables Available in Custom Lengths</p> <p>Coiled Cables Available in the Following Lengths Only:</p> <p>CB104 006 = 6 ft. (1.83 m) 010 = 10 ft. (3.05 m) 016 = 16 ft. (4.88 m)</p> <p>CB108 004 = 4 ft. (1.22 m) 006 = 6 ft. (1.83 m) 010 = 10 ft. (3.05 m) 016 = 16 ft. (4.88 m)</p>	<p>EN  Build To Order</p> <p>Isolated BNC Jack Connector Portable Measurements, Permanent Mount</p> <p>ENX  Build To Order</p> <p>Isolated BNC Jack Connector, Epoxy Filled Portable Measurements, Permanent Mount</p> <p>FN  Build To Order</p> <p>Isolated BNC Plug Connector Portable Measurements, Permanent Mount</p> <p>FNX  Build To Order</p> <p>Isolated BNC Plug Connector, Epoxy Filled Portable Measurements, Permanent Mount</p> <p>NOTE: The BNC connectors above feature a floating shield drain wire that is not case grounded</p>	<p>SF  Build To Order</p> <p>Break-Away Safety Connector</p>

