

# MH110-1A



VIBRATION ANALYSIS HARDWARE



Ultra Low Profile Flat Surface Magnet Mounting Base with 1/4-28 Threaded Blind Tapped Hole, 21 lbs. (9.5 kg) Pull Strength, 0.75 in. (18.8 mm) OD, 0.31 in. (7.7 mm) Height

## Product Features

The Industry's Lowest-Profile Solution When Paired With CTC's Miniature Side Exit Sensors

Access Readings That Were Previously Unreachable Due to Space Constraints

- ▶ Durable 17-4 stainless steel case
- ▶ High-strength neodymium iron boron magnet optimizes pull strength and performance
- ▶ Maximum frequency response up to 8 kHz (+3 dB) when paired with our UEA330 Series sensors



## Specifications

Max Temperature	266 °F (130 °C)
Case Material	17-4 Stainless Steel
Magnet Material	Neodymium Iron Boron
Dimensions	0.75 in. (18.8 mm) OD, 0.31 in. (7.7 mm) Height
Pull Strength	21 lbs. (9.5 kg)
Sensor Mounting	1/4-28 Mounting Hole

## Chemical Compatibilities for Reference

- ▶ Gasoline - A
- ▶ Methanol - A
- ▶ Lubricants - A

## Compatibility

- ▶ Compatible with all sensors with 1/4-28 mounting stud or bolt
- ▶ Conversion mounting studs sold separately

Stock Product

Backed by our Unconditional Lifetime Warranty

[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900

[www.delta3n.hu](http://www.delta3n.hu)