


# Hazardous-Area Approved DC100854 with Armor



Intrinsically Safe 25 mm PRO Proximity Probe Extension Cable, with Armored Jacket




## Product Features

### Continuous Monitoring in Hazardous Locations

PRO DC100854 extension cables combine with PRO DP100851 series probes and PRO DD1008 series drivers to form a complete assembly for monitoring Differential Expansion (DE)

- ▶ Excellent chemical resistance
- ▶ Protective sleeves to cover connection
- ▶ Upgraded to include SecureLock connector



Lengths AA, BB, and CC are configurable

## Specifications

Temperature Range	-49 to 350 °F (-45 to 177 °C)
Material	316L Stainless Steel Armor Jacket
Connector	SecureLock
Connector Pull Strength	Up to 30 lbs.
System Length	Matched to 5 & 9 meter system lengths
Bending Radius	1.16 in. (2.95 cm)

## Built to Order

## Regulatory Approvals

### US & Canada:

Class I Division 1 Groups A, B, C, D  
 Class II Division 1 Groups E, F, G  
 Class III  
 Class I Zone 0 AEx ia IIC  
 Class I Division 2 Groups A, B, C, D  
 Class II Division 2 Groups E, F, G  
 Ex ia IIC Ga

### ATEX:


SIRA 16ATEX2084X  
 Ex ia IIC

### International (IECEx):

IECEx CSA 16.0017X  
 Ex ia IIC

### Temperature Codes:

T4 = -45°C to 100°C  
 T5 = -35°C to 85°C



FOR REFERENCE ONLY, PLEASE REFER TO CONTROL DRAWING

www.delta3n.hu

Lifetime Warranty on Materials & Workmanship

www.ctconline.com | sales@ctconline.com | 585-924-5900